

DDR3L U-DIMM



Memory Module

The ADATA industrial-grade DDR3L U-DIMM memory modules feature a compact size for high speeds of 1600 MT/s, making them ideal for automation, embedded systems, networking, surveillance applications and more. In addition, the DDR3L U-DIMM memory modules operate on just 1.35V for improved power efficiency. All ADATA industrial-grade memory modules meet JEDEC and RoHS standards to ensure products with high levels of compatibility, stability, and environmental friendliness.

Features

- High speed of 1600MT/s
- Available in 2GB, 4GB, and 8GB
- Low operating voltage of 1.35V for improved power efficiency
- Customized services: 30 μ PCB gold plating, Anti-Sulfuration Protection and Conformal Coating
- Suitable for automation, embedded systems, networking, IPC, and surveillance applications
- RoHS Compliance

Ordering Information

Capacity	P/N	IC Configuration
	1600 MT/s	
2GB	ADDU1600C2G11-BSSF	256x8
4GB	ADDU1600C4G11-BSSF	256x8
4GB	ADDU1600W4G11-BSSE	512x8
8GB	ADDU1600W8G11-BSSE	512x8

*ADATA implements high-quality original ICs on its industrial-grade memory modules.

**ADATA can offer memory modules customized to the specific needs of your operations. Please contact an ADATA sales representative for a consultation.

Specifications

Model	DDR3L U-DIMM
Interface	DDR3L
Module Type	U-DIMM
Frequency	1600 MT/s
Capacity	2GB, 4GB, 8GB
Pin Count	240 Pin
PCB Height	1.18 inches/ 3cm
Operating Voltage	1.35V
Operating Temperature	0°C to 85°C
Standard	JEDEC
RoHS	Yes

Contact Us

HQ (Taiwan):

T: +886-8228-0886

E: adata@adata.com

US:

T: +1-714-332-8708

E: IASales_us@adata.com

EU:

T: +49-899-0405-296

E: IASales_eu@adata.com

China

T: +86-21-6233-1010

E: IASales_cn@adata.com

JP:

T: +81-3-5807-0011

E: IASales_jp@adata.com

APAC/MEA:

E: IASales_apacmea@adata.com